



IS standard



GROWING TOGETHER

AGRIMAX

RADIAL TRACTOR TIRES

RT 657



PRODUCT DATA SHEET



Radial

R-1W



D

181

Technologies



High Speed

Performance


Reduced Soil
Compaction


Handling and Comfort



Fuel Economy



Traction



High Load Capacity



AGRIMAX RT 657

RADIAL TRACTOR TIRES

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 16"	320/65 R 16	117 D/120 A8	W 10	W 9 ; W 11	319	822	366	2466	390	STD
Ø 18"	320/65 R 18	109 A8/B	W 10	W 9 ; W 11	319	873	392	2587	425	STD
	320/65 R 18	125 A8/B	W 10	W 9 ; W 11	310	885	400	2667	400	STD
	340/65 R 18	113 A8/B	W 11	W 10 ; W 12	343	899	400	2667	425	STD
Ø 20"	340/65 R 20	124 D/127 A8	W 11	W 10 ; W 12	343	950	430	2892	450	STD
	420/65 R 20	135 D/138 A8	W 13	W 11 ; W 12	418	1054	468	3162	500	STD
	440/65 R 20	138 D/141 A8	W 14 L	W 13 ; W 15 L	441	1080	479	3240	525	STD
Ø 24"	420/65 R 24	138 D/141 A8	W 13	W 11 ; W 12	418	1156	519	3468	550	STD
	440/65 R 24	135 D/138 A8	W 14 L	W 13 ; W 15 L	441	1182	538	3546	575	STD
	440/65 R 24	135 D/138 A8	W 14 L	W 13 ; W 15 L	441	1182	538	3546	575	SPL
	480/65 R 24	140 D/143 A8	W 15 L	W 14 L	479	1234	562	3730	600	STD
	480/65 R 24	140 D/143 A8	W 15 L	W 14 L	479	1234	562	3730	600	SPL
	540/65 R 24	146 D/149 A8	W 16 L	W 18 L	530	1312	590	3930	625	STD
	540/65 R 24	146 D/149 A8	W 16 L	W 18 L	530	1312	590	3930	625	SPL

STD: Standard - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter;
 SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index



Radial

R-1W



D

181

Technologies



High Speed

Performance

Reduced Soil
Compaction

Handling and Comfort



Fuel Economy



Traction



High Load Capacity



	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 28"	420/65 R 28	135 D/138 A8	W 13	W 11 ; W 12	418	1257	584	3824	600	STD
	440/65 R 28	138 D/141 A8	W 14 L	W 13 ; W 15 L	441	1283	590	3927	625	STD
	480/65 R 28	142 D/145 A8	W 15 L	W 14 L	479	1335	610	4091	650	STD
	540/65 R 28	149 D/152 A8	W 16 L	W 18 L	530	1413	643	4253	675	STD
	540/65 R 28	149 D/152 A8	W 16 L	W 18 L	530	1413	643	4253	675	SPL
	600/65 R 28	154 D/157 A8	DW 20 B	W 18 L	611	1491	670	4470	700	STD
	600/65 R 28	154 D/157 A8	DW 20 B	W 18 L	611	1491	670	4470	700	SPL
Ø 30"	420/65 R 30	136 D/139 A8	W 13	W 11 ; W 12	418	1308	606	3952	625	STD
	540/65 R 30	150 D/153 A8	W 16 L	W 18 L	530	1464	670	4403	700	STD
	540/65 R 30	150 D/153 A8	W 16 L	W 18 L	530	1464	670	4403	700	SPL
	600/65 R 30	155 D/158 A8	DW 20 B	W 18 L	611	1542	697	4609	725	STD
Ø 34"	540/65 R 34	152 D/155 A8	W 16 L	W 18 L	530	1566	712	4742	750	STD
	540/65 R 34	152 D/155 A8	W 16 L	W 18 L	530	1566	712	4742	750	SPL
	600/65 R 34	157 D/160 A8	DW 20 B	W 18 L	611	1644	742	4960	775	STD

STD: Standard - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index



Radial



Technologies



High Speed

Performance

Reduced Soil
Compaction

Handling and Comfort



Fuel Economy



Traction



High Load Capacity



	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 34"	600/65 R 34	157 D/160 A8	DW 20 B	W 18 L	611	1644	742	4960	775	SPL
Ø 38"	540/65 R 38	153 D/156 A8	W 16 L	W 18 L	530	1667	760	5059	800	STD
	540/65 R 38	153 D/156 A8	W 16 L	W 18 L	530	1667	760	5059	800	SPL
	600/65 R 38	159 D/162 A8	DW 20 B	W 18 L	611	1745	790	5247	825	SPL
	600/65 R 38	159 D/162 A8	DW 20 B	W 18 L	611	1745	790	5247	825	STD
	650/65 R 38	163 D/166 A8	DW 20 B	DW 21 B ; DW 23 B	645	1811	830	5483	875	SPL
	NEWSIZE									
	650/65 R 38	163 D/166 A8	DW 20 B	DW 21 B ; DW 23 B	645	1811	830	5483	875	STD
	650/65 R 38	178 A8/175 B	DW 20 B	DW 21 B ; DW 23 B	645	1816	827	5488	875	SB
	900/55 R 38	179 D/181 A8	DW 27 B	DW 30 B	880	1950	880	5842	925	STD
Ø 42"	650/65 R 42	165 D/168 A8	DW 20 B	DW 21 B ; DW 23 B	645	1913	878	5810	925	STD

STD: Standard - SPL: Special - SB: Steel Belted



Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$ - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index