



IS standard



GROWING TOGETHER

AGRIMAX

RADIAL TRACTOR TIRES

RT 765M



PRODUCT DATA SHEET



Radial



Technologies



High Speed



Steel Belted

Performance



Traction



Self-Cleaning



Reduced Soil Compaction



High Load Capacity



Handling and Comfort



AGRIMAX RT 765M

RADIAL TRACTOR TIRES

AGRIMAX RT 765M, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 38"	710/70 R 38	175 D/178 A8	DW 23 B	DW 25 B	716	1959	859	5751	925	STD
	710/70 R 38	171 D/174 A8	DW 23 B	-	716	1959	859	5751	925	STD
	710/70 R 38	166 D	DW 23 B	DW 25 B	716	1959	859	5751	925	STD
	710/70 R 38	175 D/178 A8	DW 23 B	-	716	1959	859	5751	925	SPL
	710/70 R 38	166 D	DW 23 B	DW 25 B	716	1959	859	5751	925	SPL
Ø 42"	710/70 R 42	176 D/179 A8	DW 23 B	DW 25 B	716	2061	922	6174	975	STD
	710/70 R 42	173 D/176 A8	DW 23 B	DW 25 B	716	2061	922	6174	975	STD
	710/70 R 42	173 D/176 A8	DW 23 B	DW 25 B	716	2061	922	6174	975	SPL
	710/70 R 42	176 D/179 A8	DW 23 B	DW 25 B	716	2061	922	6174	975	SPL

STD: Standard - SPL: Special



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index