



IS standard



GROWING TOGETHER

AGRIMAX

RADIAL TRACTOR TIRES

RT 945



PRODUCT DATA SHEET



Radial



Technologies



Strong Casing

Performance



High Load Capacity



Durability



Stability



Self-Cleaning




Traction



AGRIMAX RT 945

RADIAL TRACTOR TIRES

🇬🇧 AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 30"	420/90 R 30	147 A8/B	DW 13	W 14 L	418	1518	684	4571	700	STD
Ø 42"	320/90 R 42 (12.4 R 42)	139 A8/B	W 10	W 9 ; W 11	319	1643	760	4944	775	STD
Ø 46"	320/90 R 46 (12.4 R 46)	146 A8/B	W 10	W 9 ; W 11	319	1744	810	5232	825	STD
	320/90 R 46 (12.4 R 46)	148 D/151 A8	W 10	W 9 ; W 11	319	1744	810	5232	825	STD
	380/90 R 46 (14.9 R 46)	155 A8/B	W 12	W 11 ; W 13	380	1852	866	5648	875	STD
	380/90 R 46 (14.9 R 46)	159 A8/B	W 12	W 11 ; W 13	380	1852	859	5699	875	STD
Ø 50"	320/90 R 50 (12.4 R 50)	150 A8/B	W 10	W 9 ; W 11	319	1846	873	5618	875	STD
	380/90 R 50 (14.9 R 50)	151 A8/B	W 12	W 11 ; W 13	380	1954	906	5900	925	STD
	380/90 R 50 (14.9 R 50)	160 A8/B	W 12	W 11 ; W 13	390	1954	921	5958	925	STD
Ø 54"	320/90 R 54 (12.4 R 54)	156 A8/B	W 10	W 9 ; W 11	319	1948	930	6021	925	STD
	380/90 R 54 (14.9 R 54)	158 A8/B	W 12	W 11 ; W 13	380	2056	962	6232	975	STD

STD: Standard



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index