







PRODUCT DATA SHEET

Radial















Performance



Handling and Comfort













AGRIMAX SIRIO is a high-speed tire (up to 70 km/h - 45 mph) developed by BKT for high-performance tractors. Its design is perfect for both haulage and soil tillage applications. The high sidewall flexibility ensures outstanding stability, handling and comfort to improve the driving experience. It is also available with IF technology that allows to carry heavy loads at a low inflating pressure. The reinforced casing and the high number of belts guarantee great traction on the field whereas the low rolling resistance contributes to better fuel economy.

	Tire size	LI/SS	RIM Rec. Alt.		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
Ø 30 ″	540/65 R 30	150 D/147 E	W 16 L	W 18	530	1464	669	4400	700	HS
	IF 600/70 R 30	165 D/162 E	DW 21 B	DW 20 B	603	1602	713	4759	750	HS
Ø 34 ″	540/65 R 34	152 D/149 E	W 16 L	W 18	530	1566	721	4735	750	HS
Ø 38″	540/65 R 38	153 D/150 E	W 16 L	W 18 L	530	1667	769	5050	800	HS
	710/70 R 38	171 D/168 E	DW 23 B	DW 25 B	716	1959	887	5840	925	HS

HS: High Speed



 $Tolerances: O.D. \pm 2\% - S.W. \pm 2\% - RC \pm 2.5\% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; Continuous of the property of the property$ $\mathsf{SLR} = \mathsf{Static} \ \mathsf{Loaded} \ \mathsf{Radius}; \ \mathsf{RC} = \mathsf{Rolling} \ \mathsf{Circumference}; \ \mathsf{SRI} = \mathsf{Speed} \ \mathsf{Radius} \ \mathsf{Index}$

