



IS standard



GROWING TOGETHER

AGRIMAX

RADIAL TRACTOR TIRES

TERIS



PRODUCT DATA SHEET



Radial



185



AGRIMAX TERIS

RADIAL TRACTOR TIRES

Today's high-power harvesters require tires that are able to support heavy equipment and loads without damaging the crops. BKT is committed to provide you with radial tires at the cutting edge to increase your yield. AGRIMAX TERIS is the right partner for all your combined operations. Excellent traction properties and high load capacity are its essential features providing best performance in all harvesting operations. The special sidewall protection and a reinforced shoulder increase resistance – thus extending the product life-cycle – also in harsh conditions and if there are stubbles in the fields.

Technologies



Reinforced Shoulder



Special Compound



Reinforced Bead

Performance



Traction



High Load Capacity




High Puncture Resistance



Stability



Handling and Comfort

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 26"	620/75 R 26 CHO	166 A8/B	DW 20 B	-	625	1590	730	4851	750	STD
	750/65 R 26 CHO (28 L R 26)	166 A8/B	DW 25 B	DW 23 B	764	1636	713	4908	750	STD
	750/65 R 26 CHO (28 L R 26)	171 A8/B	DW 25 B	DW 23 B	764	1636	713	4908	750	STD
Ø 28"	710/55 R 28 CHO	164 A8/B	DW 23 B	-	716	1493	663	4442	700	STD
Ø 30"	620/75 R 30 CHO	168 A8/B	DW 20 B	-	625	1692	779	5169	800	STD
Ø 32"	650/75 R 32 CHO	172 A8/B	DW 21 B	DW 20 B ; DW 23 B	670	1795	816	5378	850	STD
	IF 710/75 R 32 CFO	183 A8/B	DW 25 B	DW 23 B	716	1879	851	5653	875	STD
	800/65 R 32 CHO (30.5 L R 32)	178 A8/175 B	DW 27 B	DW 25 B ; DH 27 B	818	1853	838	5551	875	STD
	900/60 R 32 CHO	181 A8/178 B	DW 27 B	DW 28 B ; DW 30 B	886	1910	854	5700	900	STD
	900/60 R 32 CHO	185 A8/182 B	DW 27 B	DW 28 B ; DW 30 B	875	1910	875	5775	900	STD
	1050/50 R 32 CHO	184 A8/181 B	36.0 VA	-	1059	1893	840	5685	875	STD
	1050/50 R 32 CHO	184 A8/181 B	36.0 VA	-	1059	1893	840	5685	875	HD
	NEWSIZE									

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index



Radial



185

Technologies



Reinforced Shoulder



Special Compound



Reinforced Bead

Performance



Traction



High Load Capacity



High Puncture Resistance




Stability



Handling and Comfort



	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 34"	IF 580/80 R 34 CFO	177 D	DW 20 B ; DW 20 A	DW 21 A ; DW 21 B	586	1792	810	5422	850	STD
	IF 710/75 R 34 CFO	184 A8/B	DW 25 B	-	716	1930	870	5852	900	STD
Ø 42"	520/85 R 42	168 D	DW 16 L	W 15 L ; DW 15 L ; DD 16 L ; W 16 L ; DD 18 L ; DW 18 L ; W 18 L	516	1951	890	5851	925	STD

STD: Standard



Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$ - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index