



IS standard



GROWING TOGETHER

AS 2001



PRODUCT DATA SHEET



Bias



R-1



A6



149

Technologies



Special Compound

Performance



Traction



High Load Capacity



Self-Cleaning



Cut and Chip Resistance



AS 2001

AS 2001 is a bias cross-ply tire which best suits tractors in soil tillage operations. Its design provides excellent traction and self-cleaning properties. AS 2001 is made of a special cut-and-chip resistant compound that also ensures great load capacity.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 22"	9.5 - 22	W 8	W 7	243	1007	470	3074	STD	8	TT	110 A6
	NEW SIZE										
Ø 26"	18.4 - 26	W 16 L	W 15 L	467	1475	650	4250	STD	10	TT	142 A6
	18.4 - 26	W 16 L	W 15 L	467	1475	650	4250	STD	10	TL	142 A6
	18.4 - 26	W 16 L	W 15 L	467	1475	650	4250	STD	12	TT	146 A6
	18.4 - 26	W 16 L	W 15 L	467	1475	650	4250	STD	12	TL	146 A6
	18.4 - 26	W 16 L	W 15 L	467	1475	650	4250	STD	14	TT	149 A6
Ø 28"	16.9 - 28	W 15 L	W 14 L	429	1420	651	4319	STD	8	TT	135 A6
	16.9 - 28	W 15 L	W 14 L	429	1420	651	4319	STD	10	TT	139 A6
	16.9 - 28	W 15 L	W 14 L	429	1420	651	4319	STD	12	TT	143 A6
	16.9 - 28	W 15 L	W 14 L	429	1420	651	4319	STD	12	TL	143 A6
	16.9 - 28	W 15 L	W 14 L	429	1420	651	4319	SPL	12	TT	143 A6

STD: Standard - SPL: Special



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference