



IS standard



GROWING TOGETHER

AT 108



PRODUCT DATA SHEET



Bias



AT 108

 AT 108 is an all-terrain tire suitable for ATVs. Its tread design provides excellent comfort and performance on-and-off the road.

Performance



Comfort



On/Off Road

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 8"	AT 20 X 7 - 8	5.5 AT	6.0 AT	170	508	-	-	STD	4	TL	-
	AT 22 X 11 - 8	9.0 AT	8.5 AT	277	560	-	-	STD	4	TL	-
Ø 9"	AT 22 X 10 - 9	8.0 AT	7.5 AT; 8.5 AT	254	559	-	-	STD	4	TL	-
	AT 22 X 11 - 9	9.0 AT	8.5 AT	275	557	-	-	STD	4	TL	-
	AT 22 X 11 - 9	9.0 AT	8.5 AT	275	557	-	-	STD	6	TL	-
	AT 25 X 12 - 9	9.5 AT	9.0 AT; 10.0 AT	292	640	-	-	STD	4	TL	-
	AT 25 X 13 - 9	10.5 AT	10.0 AT	320	635	-	-	STD	4	TL	-
	AT 25 X 13 - 9	10.5 AT	10.0 AT	320	635	-	-	STD	6	TL	-
Ø 10"	AT 20 X 10 - 10	8.0 AT	7.5 AT; 8.5 AT	250	514	235	1426	STD	4	TL	-
	AT 20 X 10 - 10	8.0 AT	7.5 AT; 8.5 AT	250	514	235	1526	STD	8	TL	-
	AT 22 X 8 - 10	6.5 AT	6.0 AT	206	557	-	-	STD	4	TL	-
	AT 22 X 8 - 10	6.5 AT	6.0 AT	206	557	-	-	STD	6	TL	-
	AT 22 X 11 - 10	9.0 AT	8.5 AT	270	564	-	-	STD	4	TL	-
	AT 22 X 11 - 10	9.0 AT	8.5 AT	270	564	-	-	STD	6	TL	-
	AT 23 X 8 - 10	6.5 AT	6.0 AT	210	594	-	-	STD	4	TL	-

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias

Performance



Comfort



On/Off Road



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 10"	AT 23 X 10 - 10	8.0 AT	7.5 AT ; 8.5 AT	259	594	-	-	STD	4	TL	-
	AT 24 X 11 - 10	9.0 AT	8.5 AT	284	608	-	-	STD	4	TL	-
	AT 24 X 11 - 10	9.0	8.5 AT	284	608	-	-	STD	6	TL	-
	AT 25 X 12 - 10	9.5 AT	9.0 AT ; 10.0 AT	298	630	-	-	STD	4	TL	-
	AT 25 X 12 - 10	9.5 AT	9.0 AT ; 10.0 AT	298	630	-	-	STD	6	TL	-
Ø 11"	AT 22 X 7 - 11	5.5 AT	-	181	557	-	-	STD	4	TL	-
	AT 23 X 8 - 11	6.5 AT	6.0 AT	191	594	-	-	STD	4	TL	-
	AT 23 X 8 - 11	6.5 AT	6.0 AT	191	594	-	-	STD	6	TL	-
	AT 24 X 8 - 11	6.5 AT	6.0 AT	206	610	-	-	STD	4	TL	-
	AT 24 X 9 - 11	7.0 AT	7.5 AT	220	605	-	-	STD	4	TL	-
	AT 24 X 9 - 11	7.0 AT	7.5 AT	220	605	-	-	STD	6	TL	-
	AT 24 X 10 - 11	8.0 AT	7.5 AT ; 8.5 AT	254	615	-	-	STD	4	TL	-
Ø 12"	AT 25 X 8 - 12	6.5 AT	6.0 AT	212	630	-	-	STD	4	TL	-
	AT 25 X 8 - 12	6.5 AT	6.0 AT	212	630	-	-	STD	6	TL	-
	AT 25 X 10 - 12	8.0 AT	6.5 AT ; 7.5 AT ; 8.5 AT	254	640	-	-	STD	4	TL	-
	AT 25 X 10 - 12	8.0 AT	6.5 AT ; 7.5 AT ; 8.5 AT	254	640	-	-	STD	6	TL	-

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference