



IS standard



GROWING TOGETHER

AT 109



PRODUCT DATA SHEET



Bias


Performance





Field Protection



AT 109

 AT 109 is an all-terrain tire for ATVs. Its tread design provides excellent field protection.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 6"	AT 145 X 70 - 6	4.5	-	137	366	-	-	STD	2	TL	-
Ø 7"	AT 16 X 8 - 7	6.5 AT	6.0 AT	183	419	-	-	STD	2	TL	-
Ø 8"	AT 18 X 9.5 - 8	7.5 AT	8.0 AT	220	468	-	-	STD	2	TL	-
	AT 20 X 7 - 8	5.5 AT	6.0 AT	170	504	-	-	STD	2	TL	-
	AT 21 X 9 - 8	7.0 AT	6.5 AT; 7.5 AT	222	536	-	-	STD	2	TL	-
	AT 22 X 11 - 8	9.0 AT	8.5 AT	230	579	-	-	STD	2	TL	-
Ø 9"	AT 25 X 12 - 9	9.5 AT	9.0 AT; 10.0 AT	269	617	-	-	STD	2	TL	-

STD: Standard



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference