



IS standard



GROWING TOGETHER

AT 110



PRODUCT DATA SHEET



Bias

Performance



Steering Control



AT 110

AT 110 is BKT's tire suitable for all-terrain applications with ATVs. Thanks to its extraordinary steering control, AT 110 is the ideal front axle tire for your vehicle.

| | Tire size | RIM | | S.W. (mm) | O.D. (mm) | SLR (mm) | RC (mm) | Version | PR | Type | LI/SS |
|-------|----------------|--------|--------|--------------|--------------|-------------|------------|---------|----|------|-------|
| | | Rec. | Alt. | | | | | | | | |
| | | | | | | | | | | | |
| Ø 8" | AT 20 X 7 - 8 | 5.5 AT | 6.0 AT | 183 | 508 | - | - | STD | 4 | TL | - |
| Ø 9" | AT 21 X 8 - 9 | 6.5 AT | 6.0 AT | 204 | 541 | - | - | STD | 4 | TL | - |
| Ø 10" | AT 21 X 7 - 10 | 5.5 AT | 6.0 AT | 178 | 531 | - | - | STD | 4 | TL | - |
| | AT 22 X 8 - 10 | 6.5 AT | 6.0 AT | 204 | 548 | - | - | STD | 4 | TL | - |
| | AT 23 X 7 - 10 | 5.5 AT | 6.0 AT | 178 | 584 | - | - | STD | 4 | TL | - |

STD: Standard



Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$ - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference