



IS standard



GROWING TOGETHER

CON STAR



PRODUCT DATA SHEET



Bias



A8



168

Technologies



Special Compound

Performance



Stability



Traction


Cut and Chip
Resistance


CON STAR

CON STAR is particularly suitable for compact loaders and telehandlers in agro-industrial, lifting and loading applications. It features great traction along with excellent vertical and horizontal stability. CON STAR has been made of a cut-and-chip-resistant compound contributing to an extended tire life-cycle.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 18"	340/80 - 18 (12.5/80 - 18)	11	12 ; 11 SDC ; 12 SDC ; W 10 ; W 11	350	1015	465	3040	IND	-	TL	143A8
Ø 20"	340/80 - 20 (12.5/80 - 20)	11	12 ; 11 SDC ; 12 SDC ; W 10 ; W 11	350	1065	491	3272	IND	-	TL	144A8
	380/75 - 20 (14.5 - 20)	W 12	W 11 ; 12 SDC ; 12 ; W 13 ; 13 SDC ; 13	385	1080	500	3273	IND	-	TL	148A8
	400/70 - 20 (16.0/70 - 20)	13	12 SDC ; 13 SDC ; 14	405	1080	501	3303	IND	16	TL	149A8
	400/70 - 20 (16.0/70 - 20)	13	12 SDC ; 13 SDC ; 14	405	1080	501	3303	IND	-	TL	156A8
	400/70 - 20 (16.0/70 - 20)	13	12 SDC ; 13 SDC ; 14	405	1080	496	3106	IND	-	TL	161A8
NEW SIZE											
Ø 24"	400/70 - 24 (16.0/70 - 24)	13	DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L	395	1175	544	3556	IND	-	TL	158A8
	400/80 - 24 (15.5/80 - 24)	DW 13	DW 12 ; DW 13 L ; DW 14 L	405	1250	570	3781	IND	20	TL	162A8
	440/80 - 24 (17.0/80 - 24)	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	455	1315	610	3986	IND	22	TL	168A8
	460/70 - 24 (17.5 L - 24)	DW 15 L	DW 14 L ; DW 16 L	460	1250	562	3784	IND	-	TL	159A8
	500/70 - 24 (19.5 L - 24)	DW 16 L	DW 15 L ; DW 18 L	505	1300	579	3926	IND	-	TL	164A8
Ø 26"	480/80 - 26 (18.4 - 26)	DW 15 L	DW 16 L	490	1410	643	4272	IND	-	TL	160A8
Ø 28"	440/80 - 28 (16.9 - 28)	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	450	1420	632	4299	IND	-	TL	156A8

IND: Industrial

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference