



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 33



PRODUCT DATA SHEET



Radial



168

Technologies



All Steel

Performance



Traction



Durability



EARTHMAX SR 33

RADIAL OTR TIRES

🇬🇧 EARTHMAX SR 33 is a radial tire for multipurpose trucks. Its multi-block tread pattern has been specially designed to guarantee extraordinary traction on soft, sandy, or muddy surfaces. EARTHMAX SR 33 provides outstanding stability in addition to best self-cleaning properties. The strong All Steel casing features excellent durability and resistance to snag and punctures.

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM	
													Rec.	Alt.
Ø 20"	14.00 R 20	TL	-	-	164/160 J	STD	-	390	1250	576	3840	23	10.0	9.0 ; 10.00 W
	335/80 R 20	TL	-	-	150 K	STD	-	335	1047	464	3145	16	11.0	-
	365/80 R 20 (14.5 R 20)	TL	-	-	152 K	STD	-	360	1096	496	3318	16	11.0	-
	395/85 R 20	TL	-	-	168 J	STD	-	394	1184	538	3589	25	10.00 W	10.00 HF

STD: Standard



Tolerances: O.D. $\pm 2\%$ - O.W. $\pm 2\%$ - RC $\pm 2.5\%$ - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference