



IS standard



GROWING TOGETHER

EM 937 E3 (L)



PRODUCT DATA SHEET



Bias



EM 937 E3 (L)

 EM 937 (E-3/L-3) has been specially designed for loaders and backhoe loaders in dig and load applications, depending on the size. It features excellent durability and provides cut and chip resistance.

Performance



Cut and Chip Resistance



Durability



Heavy Duty

	Tire size	Type	PR	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 24"	14.00 - 24	TT	20	-	STD	375	1368	628	4050	10.00 W	-
	14.00 - 24	TL	20	-	STD	375	1368	628	4050	10.00 W	-
	14.00 - 24	TT	24	-	STD	375	1368	628	4050	10.00 W	-
	14.00 - 24	TL	24	-	STD	375	1368	628	4050	10.00 W	-
	14.00 - 24	TT	28	-	STD	375	1368	628	4050	10.00 W	-
	14.00 - 24	TL	28	-	STD	375	1368	628	4050	10.00 W	-
	14.00 - 24	TT	32	-	STD	375	1368	628	4050	10.00 W	-
	14.00 - 24	TL	32	-	STD	375	1368	628	4050	10.00 W	-
Ø 25"	14.00 - 25	TT	12	-	STD	390	1368	620	4105	10.00/1.5	-
	14.00 - 25	TT	20	-	STD	375	1368	620	4105	10.00/1.5	-
	14.00 - 25	TL	20	-	STD	375	1368	620	4105	10.00/1.5	-
	14.00 - 25	TT	24	-	STD	375	1368	620	4105	10.00/1.5	-
	14.00 - 25	TL	24	-	STD	375	1368	620	4105	10.00/1.5	-
	14.00 - 25	TT	20	-	AB	375	1368	620	4105	10.00/1.5	-
	14.00 - 25	TT	20	-	A + SB	375	1368	620	4105	10.00/1.5	-
	14.00 - 25	TT	20	-	SB	375	1368	620	4105	10.00/1.5	-

STD: Standard - AB: Aramid Belted - A+SB: Aramid + Steel Belted - SB: Steel Belted

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference