



IS standard



GROWING TOGETHER

FARM HIGHWAY TOUGH



PRODUCT DATA SHEET



Bias



134

Technologies



High Speed

Performance



Durability



High Load Capacity



FARM HIGHWAY TOUGH

FARM HIGHWAY TOUGH is a high-speed tire designed for transport and soil tillage applications with trailers and implement machinery. It provides high load capacity also at high speeds and ensures a long tire life-cycle.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 15"	9.5 L - 15 FI	7.00	8 LB	245	766	343	2183	STD	8	TL	-
	9.5 L - 15 FI	7.00	8 LB	245	766	343	2183	STD	12	TL	-
	10.00 - 15 FI	8 LB	-	274	853	-	-	STD	8	TL	128 J
	11 L - 15 FI	8 LB	10 LB ; 8 J	279	777	347	2214	STD	8	TL	120 J
	11 L - 15 FI	8 LB	10 LB ; 8 J	279	777	347	2214	STD	12	TL	128 J
	12.5 L - 15 FI	10 LB	-	317	815	362	2323	STD	12	TL	134 J

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference