



IS standard



GROWING TOGETHER

FLOTATION 558



PRODUCT DATA SHEET



Bias



Performance



High Load Capacity



Durability



Traction



FLOTATION 558

FLOTATION 558 is a cross-ply flotation tire suitable for hay harvesters/balers, tankers and trailers both on and off the road. It is particularly recommended whenever traction is essential for good soil tillage in addition to high load capacity.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
												
Ø 22.5"	400/55 - 22.5	AG 11.75	12.25 ; 13.00 ; AG 13.00	405	1020	445	3084	STD	14	TL	138 A8/ 134 B	150 A8/ 146 B
	400/55 - 22.5	AG 11.75	12.25 ; 13.00 ; AG 13.00	405	1020	445	3084	STD	16	TL	140 A8/ 136 B	152 A8/ 148 B
	400/55 - 22.5	AG 11.75	12.25 ; 13.00 ; AG 13.00	405	1020	445	3084	AB HD	16	TL	140 A8/ 136 B	152 A8/ 148 B
	400/55 - 22.5	AG 11.75	12.25 ; 13.00 ; AG 13.00	405	1020	445	3084	STD	20	TL	144 A8/ 140 B	156 A8/ 152 B
	500/45 - 22.5	AG 16.00	-	500	1045	471	3167	STD	12	TL	136 A8/ 132 B	148 A8/ 144 B
	500/45 - 22.5	AG 16.00	-	500	1045	471	3167	STD	16	TL	142 A8/ 138 B	154 A8/ 150 B
	500/45 - 22.5	AG 16.00	-	500	1045	471	3167	AB HD	16	TL	142 A8/ 138 B	154 A8/ 150 B
	500/45 - 22.5	AG 16.00	-	500	1045	471	3167	STD	20	TL	146 A8/ 142 B	158 A8/ 154 B

STD: Standard - AB HD: Aramid Belted Heavy Duty



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling