



IS standard



GROWING TOGETHER

FLOTATION RIB 774



PRODUCT DATA SHEET



Bias



B



169

Performance




Durability




High Load Capacity



FLOTATION RIB 774

 FLOTATION RIB 774 is suitable in all free-rolling applications, hay harvesting applications and ideal for trailers. It has been designed to provide best handling comfort optimizing the timing of operations as well as high load capacity and a longer tire life.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.									DW
Ø 22.5"	550/60 - 22.5	AG 16.00	-	550	1240	540	3725	STD	12	TL	-	160 A8/ 156 B
	550/60 - 22.5	AG 16.00	-	550	1240	540	3725	STD	16	TL	-	167 A8/ 163 B
	600/55 - 22.5	AG 20.00	-	600	1230	540	3716	STD	16	TL	-	169 A8/ 166 B
	600/55 - 22.5	AG 20.00	-	600	1230	540	3716	STD	12	TL	-	164 A8/ 160 B

STD: Standard



Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$ - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling