



IS standard



GROWING TOGETHER

FLOTATION TR 675



PRODUCT DATA SHEET



Bias



B



168

Performance



Durability




High Load Capacity





Traction



FLOTATION TR 675

 FLOTATION TR 675 is best suited for field and road transport. It fits trailers and implement machinery. FLOTATION TR 675 has been engineered to provide outstanding traction, high load capacity and a longer tire life.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
												
Ø 22.5"	500/60 - 22.5	AG 16.00	15.00 ; 17.00	515	1181	542	3604	DB	20	TL	155 A8/ 151 B	168 A8/ 164 B
	500/60 - 22.5	AG 16.00	15.00 ; 17.00	515	1181	542	3604	STD	12	TL	145 A8/ 142 B	157 A8/ 154 B
	500/60 - 22.5	AG 16.00	15.00 ; 17.00	515	1181	542	3604	STD	16	TL	151 A8/ 148 B	163 A8/ 159 B
	550/45 - 22.5	AG 16.00	-	543	1070	-	-	STD	20	TL	154 A8/ 150 B	166 A8/ 162 B
	550/60 - 22.5	AG 16.00	-	550	1260	547	3640	STD	12	TL	148 A8/ 144 B	160 A8/ 156 B
	550/60 - 22.5	AG 16.00	-	550	1260	547	3640	STD	16	TL	154 A8/ 150 B	167 A8/ 163 B

DB: Dual Bead - STD: Standard



Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$ - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling