



IS standard



GROWING TOGETHER

FLOTATION V LINE



PRODUCT DATA SHEET



Bias



167

Performance



Field Protection




Excellent flotation








Reduced Soil Compaction



FLOTATION V LINE

 FLOTATION V LINE has been specially designed for trailers in transport applications. It shows high flotation capability and ensures low soil compaction protecting the field. FLOTATION V LINE allows you to carry high loads at low pressure maximizing your business productivity.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
												
Ø 22.5"	500/60 - 22.5	AG 16.00	15.00 ; 17.00	500	1170	510	3489	STD	12	TL	145 A8/ 142 B	157 A8/ 154 B
	500/60 - 22.5	AG 16.00	15.00 ; 17.00	500	1170	510	3489	STD	16	TL	151 A8/ 148 B	163 A8/ 159 B
	550/60 - 22.5	AG 16.00	-	550	1240	540	3725	STD	12	TL	148 A8/ 144 B	160 A8/ 156 B
	550/60 - 22.5	AG 16.00	-	550	1240	540	3725	STD	16	TL	154 A8/ 150 B	167 A8/ 163 B

STD: Standard



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling