



IS standard



GROWING TOGETHER

FL 252




PRODUCT DATA SHEET



Bias



FL 252

 FL 252 is a tire suitable for hay harvesting applications with rotor rakes/tedders as well as for logistic operations using forklifts. This tire provides excellent durability while the specific tread pattern ensures maximum stability during lifting operations.

Performance








Cut and Chip Resistance



Durability



Stability

| | Tire size | Type | PR | LI/SS | Version | S.W. (mm) | O.D. (mm) | SLR (mm) | RC (mm) | RIM | |
|-------|----------------------------|------|----|-------|---------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|--------|
| | | | | | |  |  |  |  | Rec.  | Alt. |
| Ø 8" | 5.00 - 8 | TT | 8 | - | STD | 138 | 480 | - | - | 3.00 D | 3.25 I |
| | 5.00 - 8 | TT | 10 | - | STD | 138 | 480 | - | - | 3.00 D | 3.25 I |
| Ø 9" | 6.00 - 9 | TT | 10 | - | STD | 170 | 550 | - | - | 4.00 E | - |
| Ø 10" | 6.50 - 10 | TT | 10 | - | STD | 185 | 605 | - | - | 5.00 F | 5.50 F |
| Ø 12" | 7.00 - 12 | TT | 14 | - | STD | 192 | 683 | - | - | 5.00 S | - |
| Ø 15" | 8.15 - 15 (28 X 9 - 15) | TT | 14 | - | STD | 220 | 720 | - | - | 7.00 | 7 BD |
| | 8.25 - 15 | TT | 14 | - | STD | 240 | 855 | - | - | 6.50 | 7.0 |

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference