



IS standard



GROWING TOGETHER

FL 630 SUPER



PRODUCT DATA SHEET



Radial



182



FL 630 SUPER

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

Technologies



Steel Belted



Reinforced Bead



High Speed

Performance



Durability



Field Protection



Excellent flotation



Self-Cleaning



Traction

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 22.5"	560/60 R 22.5	165 D	AG 16.00	17.00 ; 20.00	543	1244	549	3785	600	STD
	560/60 R 22.5	161 D	AG 16.00	17.00 ; 20.00	543	1244	549	3785	600	STD
	580/65 R 22.5	166 D	AG 18.00	AG 16.00 ; AG 17.00 ; AG 20.00	577	1326	594	4058	625	STD
	580/65 R 22.5	174 D	AG 18.00	AG 16.00 ; AG 17.00 ; AG 20.00	582	1326	594	4058	625	STD
	600/50 R 22.5	159 D	AG 20.00	-	611	1170	518	3533	550	STD
	600/55 R 22.5	162 D	AG 20.00	-	595	1232	560	3757	575	STD
Ø 26.5"	600/55 R 26.5	165 D	AG 20.00	-	611	1333	606	4078	625	SB
	600/55 R 26.5	177 D	AG 20.00	-	611	1333	604	4104	625	HD
	650/55 R 26.5	169 D	AG 20.00	-	645	1389	627	4258	650	STD
	650/55 R 26.5	178 D	AG 20.00	-	645	1389	628	4292	650	HD
	650/65 R 26.5	174 D	AG 20.00	-	645	1519	684	4653	725	STD
	710/50 R 26.5	170 D	AG 24.00	AG 20.00	727	1383	626	4237	650	STD
	750/45 R 26.5	170 D	AG 24.00	-	754	1349	606	4147	650	STD
	750/60 R 26.5	180 D	AG 24.00	-	754	1574	694	4800	725	STD

STD: Standard - HD: Heavy Duty - SB: Steel Belted

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index



Radial



182

Technologies



Steel Belted



Reinforced Bead



High Speed

Performance



Durability



Field Protection



Excellent flotation



Self-Cleaning



Traction



	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 30.5"	650/65 R 30.5	176 D	AG 20.00	-	645	1621	734	4976	775	STD
	710/50 R 30.5	173 D	AG 20.00	AG 24.00	686	1485	676	4550	700	SB
	NEW SIZE									
	750/60 R 30.5	181 D	AG 24.00	-	754	1675	746	5115	800	STD
	850/50 R 30.5	182 D	AG 28.00	-	860	1625	722	4895	775	STD

STD: Standard - SB: Steel Belted



Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$ - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index