



IS standard



GROWING TOGETHER

FL 630 ULTRA



PRODUCT DATA SHEET



Radial



184

Technologies



Reinforced Bead

Performance

Reduced Soil
Compaction

FL 630 ULTRA

FL 630 ULTRA is suitable for trailers, tankers and spreaders. Thanks to its reinforced bead and the particular tread design, it is the ideal tire for multipurpose use on any kind of land or on the road. FL 630 ULTRA stands for extraordinarily reduced soil compaction.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 22.5"	500/60 R 22.5	155 D/166 A8	AG 16.00	15.00 ; 16.00 ; 17.00	503	1172	521	3592	550	STD
	560/45 R 22.5	152 D/163 A8	AG 16.00	-	543	1076	490	3290	525	STD
	560/60 R 22.5	161 D/172 A8	AG 16.00	16.00 ; 17.00 ; AG 20.00	543	1244	535	3760	600	STD
	600/50 R 22.5	159 D/170 A8	AG 20.00	-	611	1172	518	3533	550	STD
	710/40 R 22.5	161 D/172 A8	AG 24.00	-	727	1140	514	3490	550	STD
Ø 26.5"	600/55 R 26.5	165 D/176 A8	AG 20.00	-	611	1333	579	4070	625	STD
	650/55 R 26.5	169 D/180 A8	AG 20.00	-	645	1389	600	4207	650	STD
	710/50 R 26.5	170 D/181 A8	AG 24.00	AG 20.00	727	1383	599	4208	650	STD
	800/45 R 26.5	174 D/184 A8	AG 28.00	AG 24.00	828	1393	618	4238	675	STD

STD: Standard



Tolerances: O.D. $\pm$ 2% - S.W. $\pm$ 2% - RC $\pm$ 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index