



IS standard



GROWING TOGETHER

FL 633 PERFORMA



PRODUCT DATA SHEET



Radial



164

Technologies



High Speed



All Steel



Strong Casing

Performance



High Load Capacity



Durability




Self-Cleaning




Multi-Purpose Tires



FL 633 PERFORMA

 The new All Steel radial tire FL 633 PERFORMA perfectly combines the needs of several agricultural applications with the growing demand for logistics in agriculture. Specifically designed for agro trucks, FL 633 PERFORMA is the innovative solution that enhances both tractor and truck performance features to meet the special needs of modern farming. Thanks to its very strong casing, exceptional load capacity and durability, FL 633 PERFORMA signs the "next level" of flotation tires being suitable for multiple activities in the fields and even for travel on highways reaching up to 100 km/h.

	Tire size	LI/SS	RIM		O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 22.5"	600/50 R 22.5	164 J	AG 20.00	-	590	1170	534	3559	-	STD

STD: Standard



Tolerances: O.D. $\pm 2\%$ - O.W. $\pm 2\%$ - RC $\pm 2.5\%$ - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index