



IS standard



GROWING TOGETHER

# FL 635



PRODUCT DATA SHEET



Radial



168

## Technologies



Reinforced Bead



High Speed

## Performance



Reduced Soil Compaction



Traction



Self-Cleaning



Durability



## FL 635

🇬🇧 FL 635 is a radial flotation tire suitable for both road and field usage. The special block pattern has been designed for hay baler applications. FL 635 ensures a great pressure distribution on the ground across the footprint and drastically reduces soil compaction to preserve the value of the crops. The tire ensures great self-cleaning properties, durability and traction along with excellent speed features.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 22.5"	500/45 R 22.5	136 D	AG 16.00	-	490	1022	461	3086	500	STD
	620/40 R 22.5	154 D	AG 20.00	-	625	1068	470	3249	500	STD
	650/55 R 22.5	167 D	AG 20.00	-	645	1287	568	3901	600	STD
	710/40 R 22.5	161 D	AG 24.00	-	727	1140	510	3467	550	STD
	750/45 R 22.5	168 D	AG 24.00	-	754	1247	555	3810	600	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index