



IS standard



GROWING TOGETHER

# FORESTECH

WIDE BASE FORESTRY TIRES



PRODUCT DATA SHEET



Bias

LS-2



A8



184

#### Technologies



Steel Belted

#### Performance



Durability



Heavy Duty



High Puncture  
Resistance



Traction



**FORESTECH**  
WIDE BASE FORESTRY TIRES

FORESTECH is a BKT bias steel-belted tire, suitable for forestry applications with forwarders. It provides excellent traction even in heavy-duty service. The strong bead and shoulder area ensure high puncture resistance as well as a longer tire life-cycle. As a result, you can deal with the most difficult operating conditions in a forest without concern.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 22.5"	710/40 - 22.5	AG 24.00	-	710	1165	550	3612	SB	20	TL	161 A8/ 165 A2
Ø 26.5"	600/55 - 26.5	AG 20.00	-	610	1335	618	4032	SB	20	TL	165 A8/ 172 A2
	710/45 - 26.5	AG 24.00	-	710	1340	620	4047	SB	20	TL	168 A8/ 175 A2
	750/55 - 26.5	AG 24.00	-	755	1485	680	4467	SB	20	TL	177 A8/ 184 A2

SB: Steel Belted



Tolerances: O.D.  $\pm 2\%$  - S.W.  $\pm 2\%$  - RC  $\pm 2.5\%$  - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference