



IS standard



GROWING TOGETHER

# GIANT TRAX



PRODUCT DATA SHEET



Bias



A8



155

## Technologies



Extra Deep Tread

## Performance

Cut and Chip  
Resistance

Durability



Heavy Duty

High Puncture  
Resistance

## GIANT TRAX

🇬🇧 GIANT TRAX has been designed for skid steer loaders in scrap yard operations, on rough concrete surfaces, recycling applications and mines. The extra deep tread with wider and sturdier blocks provides best traction, stability, and puncture resistance. The special tread compound results in exceptional cut and chip resistance along with excellent wear resistance on all types of terrains.

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 16.5"	10 - 16.5	TL	12	123 A8	IMP	270	775	362	2317	8.25	-
	10 - 16.5	TL	12	-	STD	270	775	362	2317	8.25	-
	12 - 16.5	TL	14	-	STD	315	840	398	2521	9.75	-
Ø 17.5"	14 - 17.5	TL	14	155 A2	STD	350	915	421	2714	10.50	-

IMP: Implement - STD: Standard



Tolerances: O.D.  $\pm 2\%$  - S.W.  $\pm 2\%$  - RC  $\pm 2.5\%$  - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference