



IS standard



GROWING TOGETHER

GR 288



PRODUCT DATA SHEET



Bias



GR 288

GR 288 (G-2/L-2) is a versatile bias-ply tire for graders or loaders. It is ideal for use in construction, site preparation, road building, and other soft or muddy environments. The self-cleaning tread pattern provides excellent traction, and you can expect a long tire life as a result of the special cut-and-chip-resistant compound.

Performance



Cut and Chip Resistance



Self-Cleaning



Stability



Traction

	Tire size	Type	PR	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 25"	15.5 - 25	TL	12	-	STD	385	1270	572	3772	12.00/1.3	12.00/ 1.3 (DC)
	17.5 - 25	TL	12	-	STD	445	1330	596	3950	14.00/1.5	14.00/ 1.5 (DC) ; 14.00/ 1.3 (DC)
	17.5 - 25	TL	16	-	STD	445	1330	596	3950	14.00/1.5	14.00/ 1.3 (DC)
	17.5 - 25	TT	20	-	DB HD	445	1330	596	3950	14.00/1.5	14.00/ 1.3 (DC)
	20.5 - 25	TL	16	-	STD	520	1480	656	4396	17.00/2.0	17.00/1.7
	20.5 - 25	TL	20	-	STD	520	1480	656	4396	17.00/2.0	17.00/1.7
	23.5 - 25	TL	16	-	STD	595	1610	708	4782	19.50/2.5	-
	23.5 - 25	TL	20	-	STD	595	1610	708	4782	19.50/2.5	-

STD: Standard - DB HD: Dual Bead Heavy Duty



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference