



IS standard



GROWING TOGETHER

HARVESTER SPECIAL



PRODUCT DATA SHEET



Bias



R-1



A6



191

Performance



Comfort



Cut and Chip
Resistance



Stability



Traction



HARVESTER SPECIAL

HARVESTER SPECIAL has been specifically designed for harvesters. Its dual –angled lugs provide excellent traction in the fields and a comfortable ride on the road. The special tread design provides a large contact area for extraordinary stability. HARVESTER SPECIAL features a strong casing and a particularly cut-and-chip resistant compound ensuring a longer tire life-cycle.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 25"	23.5 - 25	-	19.50/2.5	-	615	1665	715	5058	20	DB	191 A2
Ø 26"	23.1 - 26	-	DW 20 B ; DW 20 A	-	587	1585	720	4806	16	DB	159 A6

DB: Dual Bead



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference