



IS standard



GROWING TOGETHER

INDUSTRIAL RIB F3



PRODUCT DATA SHEET



Bias



A6



Technologies



Special Compound

Performance



Durability



Stubble Resistance



INDUSTRIAL RIB F3

INDUSTRIAL RIB F3 is an agro-industrial rib-pattern tire designed for field and road transport as well as for soil tillage operations with implement machinery and trailers. This tire features an outstanding stubble-resistant compound making it suitable for the most critical operating conditions and ensuring a long tire life-cycle.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 15"	11L - 15 SL	8 LB	10 LB	279	813	-	-	STD	10	TL	114A6
	11L - 15 SL	8 LB	10 LB	279	813	-	-	SR	10	TL	114A6
	11L - 15 SL	8 LB	10 LB	279	813	-	-	STD	12	TL	117A6
	11L - 15 SL	8 LB	10 LB	279	813	-	-	SR	12	TL	117A6
Ø 16"	11L - 16 SL	W 8 L	8 LB ; 10 LB ; W 10 L	279	830	-	-	SPL	10	TL	116A6
	11L - 16 SL	W 8 L	8 LB ; 10 LB ; W 10 L	279	830	-	-	STD	10	TL	116A6
	11L - 16 SL	W 8 L	8 LB ; 10 LB ; W 10 L	279	830	-	-	STD	12	TL	120A6

STD: Standard - SR: Stubble Resistant - SPL: Special



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference