



IS standard



GROWING TOGETHER

LG 408



PRODUCT DATA SHEET



Bias

Technologies



Aramid Belted

Performance



Comfort



Field Protection



High Puncture Resistance



LG 408

LG 408 is a lawn and garden tire suitable for mowers and small tractors. The specific tread pattern makes the tire gentle on the ground to prevent turf damages making handling easier at the same time. LG 408 is available in an "aramid-belted" version for users who need strengthened puncture resistance.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	24 X 13.00 - 12	10.5 I - 55 ; I - 70 ; I - 90	-	325	610	269	1755	STD	4	TL	-
	24 X 13.00 - 12	10.5 I - 55 ; I - 70 ; I - 90	-	325	610	269	1755	AB	6	TL	-
	24 X 13.00 - 12	10.5 I - 55 ; I - 70 ; I - 90	-	325	610	269	1755	STD	6	TL	-
	26.5 X 14.00 - 12	12.00 I	-	380	665	293	1929	STD	4	TL	-
	26.5 X 14.00 - 12	12.00 I	-	380	665	293	1929	AB	6	TL	-
	26.5 X 14.00 - 12	12.00 I	-	380	665	293	1929	STD	6	TL	-
	26.5 X 14.00 - 12	12.00 I	-	380	665	293	1929	STD	10	TL	-

STD: Standard - AB: Aramid Belted



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference