



IS standard



GROWING TOGETHER

# MINE STAR



PRODUCT DATA SHEET



Bias



# MINE STAR



MINE STAR is a bias-ply tire which is an excellent choice for heavy-duty underground mining operations. It features high cut/chip and puncture resistance providing improved operational efficiency. MINE STAR is made of a special compound and features a special tread design resulting in an extended tire life-cycle.

## Technologies



Extra Deep Tread

## Performance



Cut and Chip Resistance








Durability



High Puncture Resistance



Stability

	Tire size	Type	TRA CODE	PR	LI/SS	Version	TKPH	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM	
													Rec.	Alt.
														
Ø 15"	8.25 - 15	TT	-	20	-	STD	-	244	848	-	-	19	6.5	6.0 ; 7.0
	32 X 14.50 / 15 - 15	TT	-	28	-	STD	-	350	825	-	-	23	11.0	11.50 ; 11.00 BD ; 10.50
	35 X 15 - 15	TT	-	20	-	STD	-	372	885	-	-	23	11.0	11.50 ; 11.00 BD
	35 X 15 - 15	TT	-	32	-	STD	-	372	885	-	-	23	11.0	11.50 ; 11.00 BD
	35 X 15 - 15	TL	-	32	-	STD	-	372	885	-	-	23	11.0	11.50 ; 11.00 BD
	38 X 16 - 15	TT	-	32	-	STD	-	400	990	-	-	28	11.5	-
	38 X 16 - 15	TL	-	32	-	STD	-	400	990	-	-	28	11.5	-
Ø 25"	55 X 19.00 - 25	TL	L-5	50	-	STD	-	480	1400	632	4280	69	14.00	-
Ø 34"	55 X 19.00 - 34	TL	L-5	50	-	STD	-	460	1435	-	-	64	16.00	-

STD: Standard



Tolerances: O.D.  $\pm$  2% - S.W.  $\pm$  2% - RC  $\pm$  2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference