



IS standard



GROWING TOGETHER

MP 567



PRODUCT DATA SHEET



Bias



167



MP 567

🇬🇧 MP 567 is an agro-industrial tire suitable for field and road transport and municipality/maintenance operations. It is the perfect tire for telehandlers and implement machinery. The MP 567 tire provides good traction in all the weather conditions as well as excellent self-cleaning properties. This tire ensures a comfortable driving experience, together with a longer service life.

Performance



Comfort



Durability



Self-Cleaning



Traction

	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 15"	11.5/80 - 15	TL	12	123 A8	135 A8	IMP	290	875	-	-	8 LB	-
Ø 15.3"	10.0/75 - 15.3	TL	18	123 A8	135 A8	IMP	258	774	365	2401	9.0	-
	10.0/75 - 15.3	TL	10	111 A8	123 A8	IMP	258	774	365	2401	9.0	-
	10.0/75 - 15.3	TL	12	114 A8	126 A8	IMP	258	774	365	2401	9.0	-
	10.0/75 - 15.3	TL	14	118 A8	130 A8	IMP	258	774	365	2401	9.0	-
	11.5/80 - 15.3	TL	18	130 A8	143 A8	IMP	292	868	393	2578	9.0	-
	11.5/80 - 15.3	TL	10	119 A8	131 A8	IMP	292	868	393	2578	9.0	-
	11.5/80 - 15.3	TL	14	126 A8	139 A8	IMP	292	868	393	2578	9.0	-
Ø 18"	10.5 - 18	TT	10	-	-	STD	273	905	415	2768	9.0	9 SDC
	10.5 - 18	TL	10	-	-	STD	273	905	415	2768	9.0	9 SDC
	10.5 - 18	TL	12	-	-	STD	273	905	415	2768	9.0	9 SDC
	10.5 - 18	TL	12	-	-	SPL	273	905	415	2768	9.0	9 SDC
	12.0/75 - 18 (300/75 - 18)	TL	12	126 A8	139 A8	IMP	298	915	426	2723	W 9	9 ; 11
	12.5 - 18	TT	10	-	-	STD	325	990	450	2940	11.0	12 SDC
	12.5 - 18	TL	10	-	-	STD	325	990	450	2940	11.0	12 SDC
	12.5 - 18	TT	12	-	-	STD	325	990	450	2940	11.0	12 SDC

STD: Standard - SPL: Special - IMP: Implement

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling



Bias



Performance



Comfort



Durability



Self-Cleaning



Traction



	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 18"	12.5 - 18	TL	12	-	STD	325	990	466	3024	11.0	12 SDC
	12.5 - 18	TL	16	-	STD	325	990	450	2940	11.0	12 SDC
Ø 19.5"	18 - 19.5 IND	TL	16	160 B/ 162 A8	STD	460	1104	498	3280	14.00	-
	18 - 19.5 IND	TL	18	165 B/ 167 A8	STD	460	1104	498	3280	14.00	-
	18 - 19.5 IND	TL	18	165 B/ 167 A8	DB	460	1104	498	3280	14.00	-
	NEW SIZE										
Ø 20"	10.5 - 20	TT	10	-	STD	270	955	445	2880	9.0	9 SDC
	10.5 - 20	TL	10	-	STD	270	955	445	2880	9.0	9 SDC
	12.5 - 20	TT	10	-	STD	325	1040	490	3142	11.0	12 SDC
	12.5 - 20	TL	10	-	STD	325	1040	490	3142	11.0	12 SDC
	12.5 - 20	TT	12	-	STD	325	1040	490	3142	11.0	12 SDC
	12.5 - 20	TL	16	-	STD	325	1040	490	3142	11.0	12 SDC
	12.5 - 20	TL	12	-	STD	325	1040	490	3142	11.0	12 SDC
	12.5 - 20	TL	12	-	HD	325	1040	490	3142	11.0	12 SDC
	14.5 - 20	TL	10	-	STD	360	1116	495	3315	11.0	12 SDC
	14.5 - 20	TL	12	-	STD	360	1116	495	3315	11.0	12 SDC
	14.5 - 20	TL	14	-	HD	360	1116	495	3315	11.0	12 SDC

STD: Standard - HD: Heavy Duty - DB: Dual Bead

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



167

Performance



Comfort



Durability



Self-Cleaning



Traction



	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 20"	14.5 - 20	TL	16	-	STD	360	1116	495	3315	11.0	12 SDC
	14.5 - 20	TL	18	-	STD	360	1116	495	3315	11.0	12 SDC
	14.5 - 20	TL	14	-	STD	360	1116	495	3315	11.0	12 SDC
	16.0/70 - 20 (405/70 - 20)	TL	14	-	STD	405	1128	490	3350	13 SDC	12
	16.0/70 - 20 (405/70 - 20)	TT	14	-	STD	405	1128	490	3350	13 SDC	12

STD: Standard



Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$ - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference