



IS standard



GROWING TOGETHER

# MP 600



PRODUCT DATA SHEET



Bias



158

## Performance



Comfort



Durability



Self-Cleaning



Traction



## MP 600

MP 600 is an agro-industrial tire, suitable for municipality/maintenance operations with telehandlers and implement machinery, providing a comfortable driving experience. This tire provides good traction and excellent self-cleaning properties along with an extended product life-cycle.

	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 18"	10.5 - 18	TL	10	-	-	STD	272	920	420	2740	9	9 SDC
	12.5 - 18	TL	10	-	-	STD	308	990	450	2950	11	12 SDC
	12.5 - 18	TL	12	-	-	STD	308	990	450	2950	11	12 SDC
Ø 20"	400/70 - 20 (16.0/70 - 20)	TL	14	-	-	STD	405	1085	-	-	13 SDC	12
Ø 24"	400/70 - 24 (16.0/70 - 24)	TL	10	-	-	STD	405	1185	545	3530	13 SDC	12
	400/70 - 24 (16.0/70 - 24)	TL	14	-	-	STD	405	1185	545	3530	13 SDC	12
	400/70 - 24 (16.0/70 - 24)	TL	14	-	-	SPL	405	1185	545	3530	13 SDC	12
	400/70 - 24 (16.0/70 - 24)	TL	18	158 A8	-	STD	405	1185	545	3530	13 SDC	12

STD: Standard - SPL: Special



Tolerances: O.D.  $\pm$  2% - S.W.  $\pm$  2% - RC  $\pm$  2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling