



IS standard



GROWING TOGETHER

MULTIMAX

RADIAL MPT TIRES

MP 513



PRODUCT DATA SHEET



Radial



155

Technologies



High Speed



Steel Belted

Performance



Handling and Comfort



Self-Cleaning



Traction



Durability



MULTIMAX MP 513

RADIAL MPT TIRES

🇬🇧 MULTIMAX MP 513 has been designed by BKT for multi-purpose vehicles in municipality/maintenance and transport applications, for both agricultural and industrial uses. It is perfect for universal vehicles and fertilizer trucks. Thanks to the strong steel-belted nylon casing, MULTIMAX MP 513 allows to carry heavy loads at high speeds providing a comfortable driving experience. It ensures a longer service life and traction along with outstanding self-cleaning properties.

	Tire size	Type	STAR RATING	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 16"	285/80 R 16 MPT	TL	-	128 G	STD	304	866	394	2617	W 10	-
Ø 17"	425/55 R 17 MPT	TL	-	142 A8/B	STD	421	900	399	2705	13	13.00
	425/55 R 17 MPT	TL	-	134 G	STD	421	900	399	2695	13	13.00
Ø 18"	325/70 R 18 MPT	TL	-	132 G	STD	322	916	410	2771	W 10	-
	365/70 R 18 MPT	TL	-	133 G	STD	360	969	448	2954	11	11 SDC ; 12 ; 12 SDC
Ø 20"	375/70 R 20 MPT	TL	-	136 G	STD	377	1034	472	3121	12	W 10 ; DW 10 ; 11 ; 11 SDC ; W 11 ; DW 11 ; 12 SDC
	405/70 R 20 MPT	TL	-	136 G	STD	407	1076	493	3253	13	13 SDC ; 12 SDC
	425/75 R 20 MPT	TL	-	148 G	STD	421	1146	521	3479	13	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12
Ø 24"	495/70 R 24 MPT	TL	-	155 G	STD	499	1304	588	3974	W 16 L	DW 15 L ; DW 16 L ; W 15 L

STD: Standard



Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$ - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference