



IS standard



GROWING TOGETHER

MULTIMAX

RADIAL MPT TIRES

MP 515



PRODUCT DATA SHEET



Radial



160

Technologies



High Speed



Reinforced Shoulder



Steel Belted

Performance



Durability



Handling and Comfort



Self-Cleaning



Traction



MULTIMAX MP 515

RADIAL MPT TIRES

MULTIMAX MP 515 is an agro-industrial radial tire designed for universal vehicles and fertilizer trucks. It is suitable for municipality and transport applications. The tire shows a unique tread design providing superior riding comfort on the road as well as excellent self-cleaning properties and great traction. The strong steel-belted nylon casing and the reinforced shoulder ensure extraordinary durability. MULTIMAX MP 515 is the perfect tire also at high speeds (90km/h).

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 20"	405/70 R 20 MPT	136 G	13	13 SDC ; 12 SDC ; 11 SDC ; 11	407	1076	493	3286	-	STD
	425/75 R 20 MPT	148 G	13	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12	421	1146	522	3491	-	STD
Ø 22.5"	445/65 R 22.5 MPT	160 G	13	14	444	1150	527	3532	-	STD

STD: Standard



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index