



IS standard



GROWING TOGETHER

MULTIMAX

RADIAL MPT TIRES

MP 525



PRODUCT DATA SHEET



Radial



168

Technologies



All Steel

Performance



Traction

Cut and Chip
Resistance

Self-Cleaning



MULTIMAX MP 525

RADIAL MPT TIRES

MULTIMAX MP 525 is an All-Steel multi-purpose radial tire designed for universal vehicles, telehandlers, compact loaders, and graders in agro-industrial applications. The tire has been specifically developed to carry heavy loads at higher speeds both on and off the road. Indeed, the large non-directional tread design provides exceptional traction on any surface in addition to excellent self-cleaning properties. The strong sidewall ensures exceptional lateral stability in lift mode, making it the ideal choice for agricultural and material handling operations. MULTIMAX MP 525 is made of a unique, cut- and-chip-resistant tread compound that stands for a longer tire service life thanks to its extraordinary resistance against any kinds of cuts and punctures.

	Tire size	Type	STAR RATING	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 18"	405/70 R 18	TL	-	146 J/ 141 B/ 153 A2	STD	405	1025	462	3122	13	11 ; 12
	NEWSIZE										
Ø 20"	405/70 R 20 (16.0/70 R 20)	TL	-	152 J/ 168 A2	STD	405	1076	482	3260	13	12 ; 13 SDC
Ø 24"	455/70 R 24	TL	-	154 G/ 154 B/ 165 A2	STD	455	1250	571	3794	14	13 ; DW 14 L

STD: Standard



Tolerances: O.D. $\pm 2\%$ - O.W. $\pm 2\%$ - RC $\pm 2.5\%$ - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference