



IS standard



GROWING TOGETHER

# MULTI RIB



PRODUCT DATA SHEET





Bias

#### Technologies



Aramid Belted



Heavy Duty

#### Performance



Cut and Chip Resistance



Durability




High Puncture Resistance



Steering Control



# MULTI RIB

 MULTI RIB is an agro-industrial tire for soil tillage and transport applications with 2WD tractors and implement machinery. It offers excellent handling throughout its long product life-cycle. Several versions are available for every need: an "aramid belted" version with improved puncture resistance, while the "HD" is made of a special cut-and-chip resistance compound.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
											
Ø 16"	11.00 - 16	W 10 L	W 8 ; W 8 L	315	930	-	-	AB HD	12	TL	-
	11.00 - 16	W 10 L	W 8 ; W 8 L	315	930	-	-	HD	12	TL	-
	11.00 - 16	W 10 L	W 8 ; W 8 L	315	930	-	-	STD	12	TL	-

AB HD: Aramid Belted Heavy Duty - HD: Heavy Duty - STD: Standard



Tolerances: O.D.  $\pm 2\%$  - S.W.  $\pm 2\%$  - RC  $\pm 2.5\%$  - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference