



IS standard



GROWING TOGETHER

PL 801



PRODUCT DATA SHEET



Bias



PL 801

🇬🇧 PL 801 has been specially designed for hay harvesting applications with rotor rakes/tedders and for logistics operations with forklifts. It features excellent stability as well as high cut and chip resistance. PL 801 ensures an extended tire life-cycle.

Performance



Cut and Chip Resistance



Durability



Stability

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 5"	23 X 5 (23 X 5 [- 13])	3.75 P	-	154	640	-	-	STD	6	TT	-
Ø 8"	5.00 - 8	3.00 D	3.25 I	135	468	-	-	STD	8	TT	-
	5.00 - 8	3.00 D	3.25 I	135	468	-	-	STD	10	TT	-
	18 X 7 - 8 (180/70 - 8)	4.33 R	5.00 F	173	470	-	-	STD	14	TT	-
	18 X 7 - 8 (180/70 - 8)	4.33 R	5.00 F	173	470	-	-	STD	16	TT	-
Ø 9"	6.00 - 9	4.00 E	-	157	543	-	-	SPL	10	TT	-
	6.00 - 9	4.00 E	-	157	543	-	-	STD	10	TT	114A8
	6.00 - 9	4.00 E	-	157	543	-	-	STD	12	TT	-
	21 X 8 - 9 (200/75 - 9)	6.00 E	7.00 E	200	535	-	-	STD	14	TT	-
	21 X 8 - 9 (200/75 - 9)	6.00 E	7.00 E	200	535	-	-	STD	16	TT	-
Ø 10"	6.50 - 10	5.00 F	5.50 F	185	595	-	-	STD	10	TT	-
Ø 12"	7.00 - 12	5.00 S	-	189	692	-	-	STD	12	TT	-
	7.00 - 12	5.00 S	-	189	692	-	-	STD	14	TT	-

STD: Standard - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Performance

Cut and Chip
Resistance

Durability



Stability



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 15"	5.50 - 15	4.50 E DT	4.50 E SDC	157	670	-	-	STD	8	TT	-
	7.00 - 15 (29 X 8 - 15)	5.5	4.33 R ; 5.0	200	750	-	-	STD	12	TT	-
	7.00 - 15 (30 X 8 - 15)	6.0	5.50 BD ; 5.5	206	775	-	-	STD	12	TT	-
	7.00 - 15 (30 X 8 - 15)	6.0	5.50 BD ; 5.5	206	775	-	-	STD	14	TT	-
	7.50 - 15	6.0	6.00 S ; 6.5	220	785	-	-	STD	12	TT	-
	7.50 - 15 (7.50 - 15 [32" OD])	6.0	6.00 S ; 6.5	220	814	-	-	STD	14	TT	-
	7.50 - 15	6.0	6.00 S ; 6.5	220	785	-	-	STD	14	TT	-
	8.15 - 15 (28 X 9 - 15)	7.0	7.00 BD	215	720	-	-	STD	12	TT	-
	8.15 - 15 (28 X 9 - 15)	7.0	7.00 BD	215	720	-	-	STD	14	TT	-
	8.25 - 15	6.5	6.0 ; 7.0	236	854	-	-	STD	12	TT	-
	8.25 - 15	6.5	6.0 ; 7.0	236	854	-	-	STD	14	TT	-
	250 - 15 (250/70 - 15)	7.50 BD	7.0 ; 7.5	235	745	-	-	STD	16	TT	-
	250 - 15 (250/70 - 15)	7.50 BD	7.0 ; 7.5	235	745	-	-	STD	20	TT	-
	300 - 15 (315/70 - 15)	8.00 BD	8.0	295	840	-	-	STD	18	TT	-

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference