



IS standard



GROWING TOGETHER

POWER TRAX HD (FL)



PRODUCT DATA SHEET



Bias



A8



160

Technologies



Deep Tread

Performance

Cut and Chip
Resistance

Durability

High Puncture
Resistance

POWER TRAX HD (FL)

POWER TRAX HD is a premium bias-ply tire that is specially designed for forklift equipment in industrial applications. The deep tread, the extra thick sidewall and the tough casing provide exceptional durability minimizing the risk of punctures and accidental damages. The tire features excellent cut, chip and tear resistance suitable for rough and hard concrete surface. The specially designed rim guard ensures protection against flats and wheel damages in the rim flange area.

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 8"	18 X 7 - 8 (180/70 - 8)	TT	16	-	STD	173	470	-	-	4.33 R	5.00 F
	5.00 - 8	TT	10	-	STD	145	480	-	-	3.00 D	3.25 I
Ø 9"	6.00 - 9	TT	10	-	STD	166	543	-	-	4.00 E	-
Ø 10"	23 X 9 - 10 (225/75 - 10)	TT	20	-	STD	235	590	-	-	6.50 F	-
	23 X 9 - 10 (225/75 - 10)	TT	18	-	STD	235	590	-	-	6.50 F	-
	6.50 - 10	TT	12	-	STD	193	595	278	1774	5.00 F	5.50 F
	6.50 - 10	TT	14	-	STD	193	595	278	1774	5.00 F	5.50 F
	6.50 - 10	TT	10	-	STD	193	595	278	1774	5.00 F	5.50 F
Ø 12"	27 X 10 - 12 (250/75 - 12)	TT	16	-	STD	255	690	-	-	8.00 G	-
	27 X 10 - 12 (250/75 - 12)	TT	20	-	STD	255	690	-	-	8.00 G	-
	27 X 10 - 12 (250/75 - 12)	TT	20	148 A8	IMP	255	690	-	-	8.00 G	-
	27 X 10 - 12 (250/75 - 12)	TT	16	142 A8	IMP	255	690	-	-	8.00 G	-
	7.00 - 12	TT	14	-	STD	205	675	-	-	5.00 S	-
	7.00 - 12	TT	16	-	STD	205	675	-	-	5.00 S	-
Ø 15"	10.00 L - 15 (36 X 11 - 15)	TT	16	-	STD	285	918	-	-	7.50 BD	7.5

STD: Standard - IMP: Implement

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



160

Technologies



Deep Tread

Performance

Cut and Chip
Resistance

Durability

High Puncture
Resistance

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 15"	10.00 L - 15 (36 X 11 - 15)	TT	24	-	STD	285	918	-	-	7.50 BD	7.5
	250 - 15 (250/70 - 15)	TT	18	-	STD	240	745	-	-	7.50	7.0
	250 - 15 (250/70 - 15)	TT	20	-	STD	240	745	-	-	7.50	7.0
	250 - 15 (250/70 - 15)	TT	16	-	STD	240	745	-	-	7.50	7.0
	28 X 12.5 - 15	TT	24	-	STD	304	705	-	-	9.75 BD	-
	28 X 12.5 - 15	TT	24	149 A8	IMP	304	705	-	-	9.75 BD	-
	300 - 15 (315/70 - 15)	TT	20	-	STD	300	845	-	-	8.00	-
	8.15 - 15 (28 X 9 - 15)	TT	14	-	STD	227	710	-	-	7.00	7 BD
	8.25 - 15	TT	14	-	STD	248	845	-	-	6.50	7.0
	8.25 - 15	TT	16	-	STD	248	845	-	-	6.50	7.0
Ø 20"	9.00 - 20	TT	16	-	STD	270	1050	-	-	7.0	7.5
	10.00 - 20	TT	16	-	STD	285	1080	-	-	7.5	8.0
	10.00 - 20	TT	18	-	STD	285	1080	-	-	7.5	8.0
	10.00 - 20	TT	16	160 A8	IMP	285	1080	-	-	7.5	8.0

STD: Standard - IMP: Implement

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference