



IS standard



GROWING TOGETHER

PRO RIB F2M



PRODUCT DATA SHEET



Bias



Performance



Steering Control



PRO RIB F2M

PRO RIB F2M is an agricultural tire for 2WD tractors in soil tillage applications. It is particularly suitable for all operations requiring a high level of handling.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 15"	9.5 L - 15 SL	7.00	8 LB	240	780	364	2325	STD	8	TL	102A8
	11 L - 15 SL	8 LB	10 LB	280	795	370	2370	STD	8	TL	106A8
Ø 16"	10.00 - 16 SL	8 LB	W 8 L	275	894	409	2620	IND	8	TT	110A8
	10.00 - 16 SL	8 LB	W 8 L	275	894	409	2620	STD	8	TL	110A8
	10.00 - 16 SL	8 LB	W 8 L	275	894	409	2620	STD	8	TT	110A8
	11.00 - 16 SL	10 LB	W 8 L; 8 LB	335	950	440	2830	STD	8	TL	114A8
	11.00 - 16 SL	10 LB	W 8 L; 8 LB	335	950	440	2830	IND	8	TT	114A8
	11.00 - 16 SL	10 LB	W 8 L; 8 LB	335	950	440	2830	STD	8	TT	114A8
Ø 16.1"	14 L - 16.1 SL	W 11 C	-	355	980	453	2920	STD	12	TL	127A8
	16.5 L - 16.1 SL	W 14 C	W 14 CH	430	1072	-	-	STD	10	TL	129A8

STD: Standard - IND: Industrial



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference