



IS standard



GROWING TOGETHER

RIB 774 (A)



PRODUCT DATA SHEET



Bias



A8



150

Performance



Durability



High Load Capacity



RIB 774 (A)

RIB 774 (A) is a low-section implement tire offering high load capacity and a long tire life-cycle. It is suitable for hay harvesting and transport applications with balers and trailers.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
												
Ø 8"	18 X 8.50 - 8	7.00 I - 55 ; I - 70 ; I - 90	-	225	460	217	1390	AB	6	TL	-	85 A8
	18 X 8.50 - 8	7.00 I - 55 ; I - 70 ; I - 90	-	225	460	217	1390	STD	6	TL	-	85 A8
Ø 14.5"	200/60 - 14.5	AG 6.75	-	210	610	288	1888	STD	10	TT	-	106 A8
	200/60 - 14.5	AG 6.75	-	210	610	288	1888	STD	10	TL	-	106 A8
	200/60 - 14.5	AG 6.75	-	210	610	288	1888	STD	14	TT	-	113 A8
	200/60 - 14.5	AG 6.75	-	210	610	288	1888	STD	14	TL	-	113 A8
	200/60 - 14.5	AG 6.75	-	210	610	288	1888	HD	10	TT	-	106 A8
	250/65 - 14.5	AG 8.00	6.75	255	690	303	1978	STD	12	TL	-	119 A8
	250/65 - 14.5	AG 8.00	6.75	255	690	303	1978	STD	14	TL	-	124 A8
Ø 16"	10.5/65 - 16	W 9	W 8 L	265	745	339	2183	STD	14	TT	-	130 A8
	10.5/65 - 16	W 9	W 8 L	265	745	339	2183	IND	14	TT	-	130 A8
	10.5/65 - 16	W 9	W 8 L	265	745	339	2183	IND	14	TT	-	130 A8
	NEW SIZE											
Ø 18"	12.0 - 18	11.0	-	342	902	414	2688	STD	16	TL	-	150 A8

AB: Aramid Belted - STD: Standard - HD: Heavy Duty - IND: Industrial

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling