



IS standard



GROWING TOGETHER

# RIB 900



PRODUCT DATA SHEET



Bias



147

## Performance



Durability




High Load Capacity



## RIB 900

🇬🇧 RIB 900 is suitable for transport, soil tillage and hay harvesting operations with trailers, implement machinery and balers. It offers great load capacity and a long tire life-cycle.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS		
		Rec.	Alt.									DW	FR
Ø 15.5"	400/60 - 15.5	AG 13.00	-	405	875	380	2564	STD	10	TL	-	139 A8	
	400/60 - 15.5	AG 13.00	-	405	875	380	2564	STD	14	TL	-	145 A8	
	400/60 - 15.5	AG 13.00	-	405	875	380	2564	STD	16	TL	-	147 A8	

STD: Standard



Tolerances: O.D.  $\pm 2\%$  - S.W.  $\pm 2\%$  - RC  $\pm 2.5\%$  - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling