



IS standard



GROWING TOGETHER

RIDEMAX

RADIAL TRANSPORT TIRES

FL 693 M



PRODUCT DATA SHEET



Radial



182



RIDEMAX FL 693 M

RADIAL TRANSPORT TIRES

🇬🇧 RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

Technologies



Steel Belted



Reinforced Bead



High Speed



Block Pattern

Performance



Road Oriented



Durability



Fuel Economy



Self-Cleaning

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 17"	425/55 R 17	129 D/ 140 A8	13.00	-	420	894	397	2704	425	STD
	500/50 R 17	149 D/ 146 E	16.00	-	503	932	424	2913	450	STD
	VF 500/50 R 17	156 D	16.00	-	503	932	422	2880	450	STD
Ø 17.5"	400/45 R 17.5	139 D	14.00	-	400	800	343	2357	390	STD
	VF 400/45 R 17.5	142 D	14.00	-	400	800	357	2448	390	STD
Ø 22.5"	500/45 R 22.5	146 D/ 143 E	AG 16.00	-	503	1022	455	3114	500	STD
	500/60 R 22.5	155 D/ 152 E	AG 16.00	15.00 ; 17.00	503	1172	531	3577	550	STD
	500/60 R 22.5	163 D	AG 16.00	15.00 ; 17.00	503	1172	544	3625	550	STD
	560/45 R 22.5	152 D/ 149 E	AG 16.00	-	543	1076	491	3306	525	STD
	560/45 R 22.5	160 D	AG 16.00	-	543	1076	491	3306	525	STD
	560/55 R 22.5	158 D/ 155 E	AG 16.00	17.00 ; 20.00	543	1180	533	3614	550	STD
	560/55 R 22.5	162 D	AG 16.00	17.00 ; 20.00	543	1180	533	3614	550	STD
	560/60 R 22.5	161 D/ 158 E	AG 16.00	16.00 ; 17.00 ; AG 20.00	543	1244	549	3767	600	STD
	560/60 R 22.5	165 D/ 162 E	AG 16.00	16.00 ; 17.00 ; AG 20.00	543	1244	552	3767	600	STD

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index



Radial



Technologies



Steel Belted



Reinforced Bead



High Speed



Block Pattern

Performance



Road Oriented



Durability



Fuel Economy



Self-Cleaning

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 22.5"	560/60 R 22.5	169 D	AG 16.00	16.00 ; 17.00 ; AG 20.00	543	1244	552	3767	600	STD
	580/65 R 22.5	166 D/ 163 E	AG 18.00	AG 16.00 ; AG 17.00 ; AG 20.00	577	1326	572	4031	625	STD
	600/50 R 22.5	159 D/ 156 E	AG 20.00	-	611	1172	516	3574	550	STD
	650/50 R 22.5	163 D/ 160 E	AG 20.00	-	645	1222	535	3715	575	STD
	650/50 R 22.5	168 D	AG 20.00	-	645	1222	535	3715	575	STD
	710/35 R 22.5	157 D/ 154 E	AG 24.00	-	712	1070	482	3254	525	STD
	710/45 R 22.5	165 D	AG 24.00	-	706	1212	542	3658	575	STD
Ø 26.5"	600/55 R 26.5	165 D	AG 20.00	-	611	1333	586	4051	625	STD
	600/55 R 26.5	177 D	AG 20.00	-	611	1333	586	4077	625	HD
	650/55 R 26.5	169 D	AG 20.00	-	645	1389	620	4216	650	STD
	650/55 R 26.5	178 D	AG 20.00	-	645	1389	615	4250	650	HD
	710/50 R 26.5	170 D	AG 24.00	AG 20.00	727	1383	624	4217	650	STD
	710/50 R 26.5	179 D	AG 24.00	AG 20.00	727	1383	606	4217	650	HD
Ø 30.5"	600/60 R 30.5	169 D	AG 20.00	AG 18.00	605	1495	681	4495	725	STD

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index



Radial



Technologies



Steel Belted



Reinforced Bead



High Speed



Block Pattern

Performance



Road Oriented



Durability



Fuel Economy



Self-Cleaning



	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 30.5"	600/60 R 30.5	173 D	AG 20.00	AG 18.00	605	1495	681	4495	725	STD
	650/65 R 30.5	176 D	AG 20.00	-	645	1623	734	4939	775	STD
	710/50 R 30.5	173 D	AG 24.00	AG 20.00	727	1485	676	4533	700	STD
	750/60 R 30.5	181 D	AG 24.00	-	754	1675	728	5092	800	STD
	850/50 R 30.5	182 D	AG 28.00	-	862	1625	719	4925	725	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index