



IS standard



GROWING TOGETHER

RM 500



PRODUCT DATA SHEET



Radial



182

Technologies



Steel Belted

Performance



High Load Capacity



Stability




Traction

High Puncture
Resistance

RM 500

RM 500 is a steel-belted radial tire suitable for harvester implement applications. It features a strong casing and a special tread design providing high load capacity and particular cut-and-chip resistance. Thanks to its large footprint, RM 500 ensures great pressure distribution on the ground with reduced soil compaction in addition to excellent traction.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
										
Ø 24"	500/70 R 24	167 A8/155 A8	W 16 L	W 15 L	502	1310	572	3907	625	SB
	500/85 R 24	182 A8/170 A8	W 16 L	W 15 L	520	1460	622	4382	700	SB
	NEWSIZE									
	500/85 R 24	182 A8/170 A8	W 16 L	W 15 L	520	1460	622	4382	700	SB
Ø 28"	500/80 R 28	176 A8/164 A8	W 16 L	W 15 L	503	1495	635	4355	700	SB
	600/65 R 28	168 A8/156 A8	W 18 L	W 20 L	590	1486	640	4340	700	SB
	600/65 R 28	177 A8/165 A8	W 18 L	W 20 L	590	1486	640	4340	700	SB
Ø 30"	500/85 R 30	176 A8/164 A8	W 16 L	W 15 L	535	1610	674	4745	775	SB

SB: Steel Belted



Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$ - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index