



IS standard



GROWING TOGETHER

SIERRA MAX
ATV & GO KART TIRES



PRODUCT DATA SHEET



Radial



56

Technologies



M+S

Performance



Comfort



Sport



Traction



SIERRA MAX
ATV & GO KART TIRES

SIERRA MAX is the BKT tire for both all-terrain and lawn and garden applications. Its radial construction provides a significantly smoother and more comfortable ride over extreme terrains such as deserts, or dirty and rocky surfaces. The special tread design along with its wider footprint provides outstanding forward and lateral traction.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 12"	AT 25 X 8 R 12	43 N	6.50	-	206	640	292	1899	-	STD
	AT 25 X 10 R 12	50 N	8.00	-	260	640	294	1923	-	STD
Ø 14"	AT 26 X 9 R 14	48 N	7.00	-	230	675	307	2005	-	STD
	AT 26 X 11 R 14	54 N	9.00	-	280	675	310	2027	-	STD
	AT 27 X 9 R 14	50 N	7.00	-	230	700	316	2070	-	STD
	AT 27 X 11 R 14	56 N	9.00	-	280	700	318	2091	-	STD

STD: Standard



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index