



IS standard



GROWING TOGETHER

SKID POWER SK



PRODUCT DATA SHEET



Bias



138

Technologies



Deep Tread

Performance








Durability



SKID POWER SK

 SKID POWER SK has been specially designed for skid steers in construction applications. Its sidewall and rim guard protectors as well as its deep tread provide an extended tire life-cycle.

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 16.5"	10 - 16.5	TL	10	-	STD						
	10 - 16.5	TL	8	-	STD	270	775	355	2286	8.25	-
	10 - 16.5	TL	12	138 A2	STD	270	775	355	2286	8.25	-
	10 - 16.5	TL	8	116 A8	IMP	270	775	355	2286	8.25	-
	10 - 16.5	TL	10	120 A8	IMP	270	775	355	2286	8.25	-
	12 - 16.5	TL	12	-	STD	312	825	375	2434	9.75	-
	12 - 16.5	TL	10	-	STD	312	825	375	2434	9.75	-
	12 - 16.5	TL	10	125 A8	IMP	312	825	375	2434	9.75	-
	12 - 16.5	TL	12	130 A8	IMP	312	825	375	2434	9.75	-

STD: Standard - IMP: Implement



Tolerances: O.D. $\pm 2\%$ - S.W. $\pm 2\%$ - RC $\pm 2.5\%$ - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference