



IS standard



GROWING TOGETHER

SKID POWER



PRODUCT DATA SHEET



Bias



141

Performance

Cut and Chip
Resistance

Self-Cleaning



Traction



SKID POWER

SKID POWER has been designed for skid steers in construction applications. It shows excellent traction as well as enhanced self-cleaning features. The tire features an extra deep tread along with extra sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER is the ideal tire for loose surfaces.

	Tire size	Type	PR	LI/SS		Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
				DW	FR						Rec.	Alt.
Ø 12"	23 X 10.5 - 12	TL	6	90 A8	90 A8	IMP	264	590	-	-	8.5 I - 55	7.00 I - 55 ; I - 70 ; I - 90
Ø 14"	25 X 8.5 - 14	TL	6	106 A2		STD	213	652	305	1912	7 JA	-
Ø 16.5"	10 - 16.5	TL	8	-		STD	254	775	355	2286	8.25	-
	10 - 16.5	TL	10	-		STD	254	775	355	2286	8.25	-
	10 - 16.5	TL	8	116 A8		IMP	254	775	355	2286	8.25	-
	12 - 16.5	TL	10	-		STD	305	821	373	2422	9.75	-
	12 - 16.5	TL	10	125 A8		IMP	305	821	373	2422	9.75	-
Ø 17.5"	14 - 17.5	TL	14	-		STD	355	940	424	2773	10.5	-
	14 - 17.5	TL	14	141 A8		IMP	355	940	424	2773	10.5	-

STD: Standard - IMP: Implement



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference