



IS standard



GROWING TOGETHER

# SM 54 L4S IND-4S



PRODUCT DATA SHEET



Bias



# SM 54 L4S IND-4S

🇬🇧 SM 54 (L-4S) IND-4S has been specially designed for empty container handlers and reach stackers in intermodal/logistics applications. It features high stability in lift mode as well as a deep and smooth tread design, providing excellent cut resistance to ensure an extended tire life-cycle.

## Technologies



Heavy Duty

## Performance



Cut and Chip Resistance



Durability



Hard Surfaces



Stability

	Tire size	Type	PR	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec. 	Alt.
Ø 25"	16.00 - 25	TL	28	-	IND	430	1470	676	4354	11.25/2.0	13.00/2.0
	16.00 - 25	TL	32	-	IND	430	1470	676	4354	11.25/2.0	13.00/2.0

IND: Industrial



Tolerances: O.D.  $\pm 2\%$  - O.W.  $\pm 2\%$  - RC  $\pm 2.5\%$  - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference