



IS standard



GROWING TOGETHER

SUPER GRADER



PRODUCT DATA SHEET



Bias

G-2



Technologies



Special Compound

Performance



Durability



Heavy Duty



Self-Cleaning



Traction



SUPER GRADER

🇬🇧 SUPER GRADER (G-2) is a bias tire particularly designed for graders. It shows excellent traction and self-cleaning features. SUPER GRADER is made of a special compound which enables an extended tire life-cycle and heavy-duty service.

	Tire size	Type	TRA CODE	PR	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM	
													Rec.	Alt.
														
Ø 24"	13.00 - 24	TL	G-2	12	-	STD	-	340	1275	588	3800	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC
	13.00 - 24	TL	G-2	16	-	STD	-	340	1275	588	3800	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC
	13.00 - 24	TT	G-2	12	-	STD	-	340	1275	588	3800	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC
	13.00 - 24	TT	G-2	16	-	STD	-	340	1275	588	3800	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC
	14.00 - 24	TT	G-2	12	-	STD	-	364	1335	598	3952	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00 VA SDC ; 10.00 WA SDC
	14.00 - 24	TT	G-2	16	-	STD	-	364	1335	598	3952	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC
	14.00 - 24	TL	G-2	12	-	STD	-	364	1335	598	3952	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00 VA SDC ; 10.00 WA SDC
	14.00 - 24	TL	G-2	16	-	STD	-	364	1335	598	3952	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC
	16.00 - 24	TL	G-2	16	-	STD	-	430	1450	644	4307	29	10.00 VA SDC	-

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference