



IS standard



GROWING TOGETHER

TRAC GRADER +



PRODUCT DATA SHEET



Bias



TRAC GRADER +

TRAC GRADER + (G-2) is a bias-ply tire for graders. It is an excellent choice for the budget-minded customers. The durable casing is designed to last. The self-cleaning tread design shows open lug-to-void-ratio which provides best traction in all conditions. Its "special" version is made of a special cut-and-chip-resistant compound.

Performance



	Tire size	Type	TRA CODE	PR	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM	
													Rec.	Alt.
														
Ø 24"	13.00 - 24	TL	G-2	12	-	STD	-	340	1280	600	3943	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00VA SDC
	13.00 - 24	TL	G-2	14	-	STD	-	340	1280	600	3943	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00VA SDC
	13.00 - 24	TL	G-2	16	-	STD	-	340	1280	600	3943	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00VA SDC
	13.00 - 24	TL	G-2	12	-	SPL	-	340	1280	600	3943	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00VA SDC
	14.00 - 24	TL	G-2	12	-	STD	-	364	1348	598	3990	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00 VA SDC ; 10.00 WA SDC
	14.00 - 24	TL	G-2	16	-	STD	-	364	1348	598	3990	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00VA SDC
	14.00 - 24	TT	G-2	12	-	STD	-	364	1348	598	3990	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00 VA SDC ; 10.00 WA SDC
	14.00 - 24	TT	G-2	16	-	STD	-	364	1348	598	3990	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00VA SDC
	14.00 - 24	TL	G-2	12	-	SPL	-	364	1348	598	3990	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00VA SDC ; 10.00 WA SDC
	14.00 - 24	TL	G-2	16	-	SPL	-	364	1348	598	3990	25	8.00 TG SDC	9.00/1.5 (DC) ; 10.00VA SDC

STD: Standard - SPL: Special



Tolerances: O.D. $\pm$ 2% - O.W. $\pm$ 2% - RC $\pm$ 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference