



IS standard



GROWING TOGETHER

TRAC MASTER



PRODUCT DATA SHEET



Bias

Performance



Field Protection



Self-Cleaning



Traction



TRAC MASTER

TRAC MASTER is a soil tillage and lawn and garden tire, suitable for small tractors and implement machinery. Its tread design provides excellent field protection along with great traction in the fields and optimum self-cleaning properties.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 12"	300/60 - 12	10.5	9.5	306	645	285	1885	STD	8	TL	-
Ø 15"	31 X 15.50 - 15	13 LB	-	405	792	370	2372	STD	6	TL	-
	31 X 15.50 - 15	13 LB	-	405	792	370	2372	STD	8	TL	-
	33 X 15.50 - 15	13 LB	-	404	865	378	2526	STD	6	TL	-
	33 X 15.50 - 15	13 LB	-	404	865	378	2526	STD	8	TL	-
	380/50 - 15	13 LB	-	380	780	364	2229	STD	8	TL	116 B

STD: Standard



Tolerances: O.D. \pm 2% - S.W. \pm 2% - RC \pm 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference