



IS standard



GROWING TOGETHER

TR 136



PRODUCT DATA SHEET



Bias



R-1



A6



151

Technologies



Special Compound



More Lugs

Performance

Cut and Chip
Resistance

Durability



High Load Capacity



Traction



TR 136

🇬🇧 TR 136 has been developed by BKT to equip tractors and trailers in soil tillage and haulage operations. This tire provides improved traction in all working conditions along with best cut and chip resistance to reduce machine downtime and increase your productivity. Thanks to the increased number of lugs, TR 136 provides outstanding traction even at high loads.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 26"	18.4 - 26	W 16 L	W 15 L	480	1450	646	4205	SPL	12	TL	146 A6
	18.4 - 26	W 16 L	W 15 L	480	1450	646	4205	STD	14	TL	150 A6
	18.4 - 26	W 16 L	W 15 L	480	1450	646	4205	STD	12	TL	146 A6
	18.4 - 26	W 16 L	W 15 L	480	1450	646	4205	STD	12	TT	146 A6
Ø 28"	12.4 - 28	W 11	W 9; W 10	315	1275	595	3749	STD	8	TT	123 A6
Ø 30"	16.9 - 30	W 15 L	W 14 L	429	1485	677	4455	HD	8	TT	137 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	687	4523	SPL	12	TT	143 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	677	4455	SPL	8	TT	137 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	687	4523	SPL	12	TL	143 A6
	16.9 - 30 (14 - 30)	W 15 L	W 14 L	429	1485	677	4455	STD	14	TT	146 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	677	4455	STD	8	TT	137 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	677	4455	STD	10	TT	139 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	687	4523	STD	12	TT	143 A6
	18.4 - 30	W 16 L	W 15 L	467	1550	712	4719	HD	8	TT	139 A6
	18.4 - 30	W 16 L	W 15 L	467	1550	712	4719	HD	12	TT	149 A6
	18.4 - 30	W 16 L	W 15 L	467	1550	712	4719	HD	14	TT	151 A6
	18.4 - 30	W 16 L	W 15 L	467	1550	712	4719	SPL	12	TT	149 A6
	18.4 - 30	W 16 L	W 15 L	467	1550	712	4719	STD	8	TT	139 A6

SPL: Special - STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter;
SLR = Static Loaded Radius; RC = Rolling Circumference